



**BuildMan**  
Grade

**FIBERGLASS  
LADDER AND  
STEP LADDERS**

**HEAVY-DUTY**

- Electrical and thermal insulator
- Resistant to corrosion
- Durable
- Lightweight

**METALTECH**



TYPE  
**IA**  
300 LB

**INDUSTRIAL**



**BUILT TOUGH FOR  
SAFETY**



Metaltech has been providing safe access solutions since 1960. Expanding into the ladder product line was a natural progression for the company. You can trust Metaltech for your safety at heights.

Buildman grade by Metaltech: A combination of quality and sturdiness for Pros. The Metaltech Buildman products are part of the Premium Construction offering available on the market. This product line features high-quality units designed to provide a robust and durable solution for Pro-users.

### WHY CHOOSE A FIBERGLASS LADDER?

It's a non-conductive, lightweight, and durable material that serves as an electrical and thermal insulator while remaining corrosion-resistant in various weather conditions.

- Electrical and thermal insulator
- Resistant to corrosion
- Durable
- Lightweight



MULTI-FUNCTIONAL MOLDED TOP WITH VERSATILE TOOL SLOTS

INSIDE SPREADER BRACES TO PROTECT AGAINST FINGER PINCHING

SLIP RESISTANT STEPS DOUBLE-RIVETED FOR MORE RIGIDITY

FIBERGLASS

HEAVY DUTY FEET SLIP RESISTANT

FIBERGLASS




RUNG LOCK  
• TOUGH  
• STRONG  
• LIGHT

END CAP  
• NON-MARKING  
• DURABLE

D-RUNG ANTI-SLIP TEXTURIZED RUNG



SWIVEL RUBBER FEET  
• SELF-LEVELLING  
• GROUND ANCHORING SPIKES

FIBERGLASS STEP LADDER	4'	6'	8'	FIBERGLASS LADDER	24'
OPEN DIMENSIONS (W X D X H)	20.25 X 28.25 X 46 IN. (51.4 X 71.8 X 116.8 CM)	23.75 X 39.75 X 69 IN. (60.3 X 101 X 175.3 CM)	27 X 51.25 X 91.75 IN. (68.6 X 130.2 X 233 CM)	LENGTH OF SECTIONS	12 FT (3.7 M)
CLOSED DIMENSIONS (W X D X H)	20.25 X 6.5 X 50 IN. (51.4 X 16.5 X 127 CM)	23.75 X 6.5 X 74 IN. (60.3 X 16.5 X 188 CM)	27 X 6.5 X 97.5 IN. (68.6 X 16.5 X 247.7 CM)	MAX. EXTENDED LENGTH	21 FT (6.4 M)
STEP LADDER SIZE	4 FT (1.2 M)	6 FT (1.8 M)	8 FT (2.4 M)	MAX. WORKING LENGTH**	24 FT 3 IN. (7.4 M)
MAXIMUM WORKING LENGTH**	8 FT 8 IN. (2.6 M)	10 FT 6 IN. (3.2 M)	12 FT 5 IN. (3.8 M)	HIGHEST STANDING LEVEL	17 FT 6 IN. (5.3 M)
HIGHEST STANDING LEVEL	1 FT 11 IN. (0.6 M)	3 FT 9 IN. (1.1 M)	5 FT 8 IN. (1.7 M)	LOAD CAPACITY*	300 LB (136 KG)
STEP DEPTH	3 IN. (7.6 CM)	3 IN. (7.6 CM)	3 IN. (7.6 CM)	WEIGHT	51.6 LB (23.4 KG)
LOAD CAPACITY*	300 LB (136 KG)	300 LB (136 KG)	300 LB (136 KG)	STANDARDS	ANSI TYPE IA, CSA GRADE 1A
WEIGHT	15.2 LB (6.9 KG)	20.2 LB (9.2 KG)	26.5 LB (12 KG)	MATERIAL	FIBERGLASS
STANDARDS	ANSI TYPE IA AND CSA CERTIFIED GRADE 1A 	ANSI TYPE IA AND CSA CERTIFIED GRADE 1A 	ANSI TYPE IA AND CSA CERTIFIED GRADE 1A 	MODEL	E-ELFB24T1A
MATERIAL	FIBERGLASS	FIBERGLASS	FIBERGLASS	UPC	778300007783
MODEL	E-SLFB4T1A	E-SLFB6T1A	E-SLFB8T1A	*Load capacity: Includes weight of user plus materials **Max. reach: Calculated with a 5'-9" (1.75 m) person with a vertical 12" (30 cm) reach	
UPC	778300008469	778300007769	778300007776		