

**SAFE AND
MULTI-PURPOSE
FALL PREVENTION**

WARNING LINE

METALTECH[®]

POLYVALENT AND SAFE SYSTEM

- Yellow cable or rope with high visibility pennants
- Delimits risk areas and work site access
- Quick and low-cost installation
- Safety add-on to your Metaltech guardrail system



**BUILT TOUGH FOR
SAFETY**

5

REASONS TO CHOOSE

THE METALTECH WARNING LINE

1

QUICK SETUP. NO PERFORATIONS OF THE ROOF

2

DURABLE AND RESISTANT

3

CAPACITY TO CONVERT THE WARNING LINE TO A REGULAR GUARDRAIL

4

HIGH VISIBILITY IN THE FOG AND IN SNOW STORMS

5

LOW-COST SAFETY SOLUTION



DELIMITS A SAFE WORK AREA

To protect escarpments or any trench more than 3 meters that can be a source of danger.



SAFER ROOF OR DECK WORK

The warning line is used to define a work area at least 2 meters from any place where a worker is at risk of falling.

NYLON ROPE WITH PENNANTS

DIMENSIONS	98 ft (30 m)
WEIGHT	1.58 lb (0.72 kg)
MATERIAL	Nylon rope
COMPLIES TO	CNB, CSTC, CNESST, ANSI, RSST, OBC
COLOR	Yellow
PENNANTS	Integrated to the rope 7 X 10 ft (18 X 25 cm)
INSTALLATION	Quick and directly on the hook clamp. Permanent or temporary.
COMPATIBLE	Standard system and stackable
MODEL	M-MTWLR



NYLON COATED STEEL WIRE WITH CARABINERS

DIMENSIONS	8 ft (2.4 m)
WEIGHT	0.95 lb (0.43 kg)
MATERIAL	Nylon coated steel wire
COMPLIES TO	CNB, CSTC, CNESST, ANSI, RSST, OBC
COLOR	Yellow
INSTALLATION	Quick installation, with carabiners on the hook clamp. Permanent or temporary.
COMPATIBLE	Standard system and stackable
MODEL	M-MTWLC8



PLASTIC PENNANT

DIMENSIONS	6.5 x 9 in. (16.5 x 22.8 cm)
WEIGHT	0.13 lb (0.06 kg)
MATERIAL	Plastic
COMPLIES TO	CNB, CSTC, CNESST, ANSI, RSST, OBC
COLOR	Yellow
INSTALLATION	Clip in the center of pre-existing crimps on steel wires, preventing lateral displacement.
COMPATIBLE	Standard system and stackable
MODEL	M-MTWLFPL



ROOF SNOW REMOVAL

Fast installation to make the snow removal area safe. The warning line is the best solution on commercial roofs.



WWW.METALTECH.CO

1 800 363-7587