



JOBSITE SERIES™ DRYWALL STILTS

- One piece rubber sole
- Dual spring action for more flexibility
- Secure self-locking metal buckle straps
- Adjustable Height
- Reach up to 10 ft with tallest model

METALTECH®

**BUILT TOUGH FOR
SAFETY**

JOBSITE SERIES™ DRYWALL STILTS

The Metaltech Jobsite Series Drywall Stilts are one of our most valuable tools. Built on a one-piece rubber sole that ensure great contact and grip on the ground it is made of an aluminum frame. These stilts are perfect to reach higher levels and walking freely as if you were on the ground. Their dual spring action provides maximum flexibility and a natural walking feel.

The stilts can easily be adjusted to reach the desired height and hold up to 225 lb load capacity.



18-30 IN. DRYWALL STILTS

ASSEMBLED DIMENSIONS (1 STILT) (WXDXH)	12.5 X 6 X 38 IN. (31.8 X 15.2 X 96.5 CM)
ADJUSTABLE HEIGHTS	18 UP TO 30 IN. (45.7 UP TO 76.2 CM) 2 IN. (5 CM) INCREMENT ADJUSTABLE HEIGHTS.
MAXIMUM REACH*	9 FT 3 IN. (2.82 M)
WEIGHT (1 STILT)	7.1 LB (3.2 KG)
LOAD CAPACITY	225 LB (102 KG)
MODEL	I-IDS1830
UPC	778300006854



24-40 IN. DRYWALL STILTS

ASSEMBLED DIMENSIONS (1 STILT) (WXDXH)	12.5 X 6 X 44 IN. (31.8 X 15.2 X 111.8 CM)
ADJUSTABLE HEIGHTS	24 UP TO 40 IN. (61 CM UP TO 1.02 M) 2 IN. (5 CM) INCREMENT ADJUSTABLE HEIGHTS.
MAXIMUM REACH*	10 FT (3.05 M)
WEIGHT (1 STILT)	8.1 LB (3.7 KG)
LOAD CAPACITY	225 LB (102 KG)
MODEL	I-IDS2440
UPC	778300006908

*Calculated with a 5'9" (1.75 m) person with a vertical 12" (30 cm) reach

STRAPS DURABLE, FULLY ADJUSTABLE AND SECURE

ADJUSTABLE ALUMINUM TUBE PROVIDES A PERFECT LEG FITTING

SECURE SELF-LOCKING METAL BUCKLE STRAPS

ALL ALUMINUM LIGHT WEIGHT CONSTRUCTION

DUAL SPRING ACTION FOR MORE FLEXIBILITY AND NATURAL WALKING FEEL

ADJUSTABLE HEIGHTS

CONTACT GRIP ONE PIECE RUBBER OUTSOLE



METALTECH®

WWW.METALTECH.CO

1 800 363-7587

Metaltech is a registered trademark of Metaltech-Omega inc. | www.metaltech-omega.com | NOTE: Pictures and descriptions in this brochure may differ from actual product. S-IDS-NA-EN01