

BuildMan Grade SAFESPACE PLATFORM FIBERGLASS STEP LADDER

The platform makes this unit the number one choice for constant work at heights, increasing user comfort. Reducing fatigue, it gives the user the sensation and stability of working on the ground. If needed, you can lean on the upper bar at hip level for maximum comfort and support. Multiple step ladder sizes are available to work at heights confidently over an extended period of time.



	8' REACH	9' REACH	10 ' REACH
OPEN DIMENSIONS (W X D X H)	25.75 X 30.75 X 57.75 IN. (65.4 X 78.1 X 146.7 CM)	27.25 X 37.25 X 69 IN. (69.2 X 94.6 X 175.3 CM)	29 X 43.25 X 80.5 IN. (73.7 X 109.9 X 204.5 CM)
CLOSED DIMENSIONS (W X D X H)	25.75 X 8.75 X 62.75 IN. (65.4 X 22.2 X 159.4 CM)	27.25 X 8.75 X 75 IN. (69.2 X 22.2 X 190.5 CM)	29 X 8.75 X 87 IN. (73.7 X 22.2 X 221 CM)
NOMINAL SIZE	2 FT (0.6 M)	3 FT (0.9 M)	4 FT (1.2 M)
MAXIMUM REACH*	8 FT 8 IN. (2.6 M)	9 FT 8 IN. (3 M)	10 FT 7 IN. (3.2 M)
HIGHEST STANDING LEVEL	1 FT 11 IN. (0.6 M)	2 FT 11 IN. (0.9 M)	3 FT 10 IN. (1.2 M)
PLATFORM DIMENSIONS	16.5 X 16.5 IN. (41.9 X 41.9 CM)	16.5 X 16.5 IN. (41.9 X 41.9 CM)	16.5 X 16.5 IN. (41.9 X 41.9 CM)
STEP DEPTH	3 IN. (7.6 CM)	3 IN. (7.6 CM)	3 IN. (7.6 CM)
LOAD CAPACITY**	300 LB (136 KG)	300 LB (136 KG)	300 LB (136 KG)
WEIGHT	23.8 LB (10.8 KG)	28.3 LB (12.8 KG)	32.9 LB (14.9 KG)
STANDARDS	ANSI TYPE IA, CSA GRADE 1A	ANSI TYPE IA, CSA GRADE 1A	ANSI TYPE IA, CSA GRADE 1A
MATERIAL	FIBERGLASS	FIBERGLASS	FIBERGLASS
MODEL	E-PSFB2T1A	E-PSFB3T1A	E-PSFB4T1A
UPC	778300007974	778300007981	778300007998

*Max. reach: Calculated with a 5'-9" (1.75 m) person with a vertical 12" (30 cm) reach **Load capacity: Includes weight of user plus materials



<u>www</u>.metaltech.co

1 800 363-7587